



<b>Model name</b>	ENKI
<b>Pixel pitch</b>	0.9375 mm
<b>Brightness</b>	≥ 1200 nit
<b>Pixel density</b>	640 x 360 px/cabinet; 1,137,778 px/m <sup>2</sup>
<b>LED-type</b>	COB (Chip-on-Board), Flip Chip
<b>Lifespan LED</b>	100,000 hours
<b>Viewing angle</b>	160° horizontal; 160° vertical
<b>Input frequency</b>	50 to 60 Hz
<b>Processing</b>	Novastar, CA50E (5G) Receiving Card
<b>Bit depth</b>	16 bit
<b>Refreshrate</b>	7680
<b>Power consumption</b>	Maximum: 480 W/m <sup>2</sup> Average: 160 W/m <sup>2</sup>
<b>Input voltage</b>	100 - 240 V / 50 - 60 Hz
<b>Temperature operating</b>	0 to 45 C°
<b>Humidity operating</b>	10 to 90 %
<b>Cabinet dimensions</b>	600 x 337 x 77 mm (WxHxD); (=0.20 m <sup>2</sup> )
<b>Weight</b>	7.2 kg/cabinet
<b>Maintenance</b>	Front/Back maintenace
<b>Protection</b>	IP30
<b>Certification</b>	CE, RoHs, EMC class B, TÜV